

The versatile TrackWall System accessories sold by Closet Works as part of the Omni Track Organization system are easy and quick to install or remove.

- To install a new hook or accessory, simply position and place the hook on the track wall and finish off with the cover cap. Installing the Cover Cap is imperative to prevent the accessory from becoming dislodged from the track and falling. The cover cap secures the accessory to the track wall, while still allowing you to slide and reposition the hook horizontally.
- To remove an accessory, reverse the process and take off the cover cap, being careful not to break it, as you will need it again if you intend to reuse the accessory. Once the cover cap is off, you will be able to lift off the accessory.
- A video demonstration is available on our website under the "How To" section: www.closetworks.com/installation-help.shtml

HOW TO ADD OR INSTALL OMNI TRACK GARAGE ACCESSORIES ONTO YOUR TRACKWALL SYSTEM

Heavy Duty Accessory Installation



Cover Cap



1 Align the accessory with the wall track and gently pull down until you feel it seat itself into the groves.



2 Align the cover cap with the sides of the accessory and the hole in the middle.



3 Push and snap it into place.



4 Your accessory will be able to move along the track horizontally for repositioning, but will not fall off as long as the cover cap remains in place.

Light Duty Accessory Installation



Cover Cap



1 Align the top of the accessory with an extruded section of the track. The top hooks over the extrusion and the bottom slips under the next extrusion below.



2 Align the cover cap with the accessory. This is what keeps the accessory secured to the track



3 Push and snap it into place.



4 Your accessory will be able to move along the track horizontally for repositioning, but will not fall off as long as the cover cap remains in place.

REMOVAL OF ACCESSORIES:

Heavy Duty Accessory Removal



Cover Cap



1 To remove your accessory, you must first remove the cover cap.



2 Hold the cap from top and bottom, and pull towards yourself.



3 There are wings on the sides of the cover cap. Be careful not to break these during removal, as they hold the cap and the accessory in place.



4 You can now lift and remove the accessory from the aluminum track wall.

Light Duty Accessory Removal



Cover Cap



1 To remove your accessory, you must first remove the cover cap.



2 Hold the cap from the top, using the other hand push out gently from the bottom side.



3 Carefully remove the cover cap, being careful not to break it.



4 Lift and remove the accessory from the aluminum track wall.